

**HEAT AND CONTROL**

®

## Gentle-Flo® Produce Transport & Bin Storage System

Reduce labor costs and product damage with this automatic produce transfer and storage system.



*Bins are available in painted or stainless steel construction with a belt or auger discharge.*

### Gentle handling

Gentle-Flo® automatically transports potatoes and other produce from your receiving area to short-term storage bins and then on to the processing line. Product damage is reduced by gentle handling which minimizes drops and abusive transfer points.

### Convey or flume

Choose a belt conveyor or water flume to transfer product to and from the storage bins. Dirt and debris removers, sizers and inspection conveyors are available for either transfer system.

### Large capacity, less space

Requiring minimal floor space, standard bins hold 1,350 cubic feet of product. Custom bin sizes are also available.

### Adjustable discharge

Each bin has its own variable speed discharge for metered output or to proportionally mix products from different bins.

### Low maintenance

Robust epoxy painted steel or optional stainless steel construction provides a long and reliable service life.

*Water flume systems save floor space and wash product as it is transported from our Truck Dumper to the Gentle-Flo storage bins.*



# Gentle-Flo® Produce Transport & Bin Storage System

Model GF



## Gentle-Flo Bin Capacities

Product	Bulk Density		Bin Capacity
	Lbs/Cu Ft	Kg/Cu M	
Potatoes	45		60,750
	721		27,581
Carrots	35		47,250
	561		21,460
Onions	46		62,100
	737		28,193
Beets	44		59,400
	705		26,968
Apples	32		43,200
	513		19,617
Pears	39		52,650
	625		23,903
Oranges	29		39,150
	465		17,774

Based on standard bin capacity of 1,350 cu. ft. Custom bin capacities are available. Product densities are approximate.

Constant improvement and engineering innovations mean these specifications may change without notice.

Horizontal Bin Filling  
Auger gently sweeps product from the Horizontal Apportioning Conveyor into the pre-selected bin.



Filling stops automatically when the bin reaches capacity. The Bin Filling Auger levels product and begins filling the next preselected bin.

Angled rubber "Lowerators" let product gently descend into the bin to minimize impact damage.

**HEAT AND CONTROL**

®



Headquarters  
21121 Cabot Blvd., Hayward, CA 94545 USA  
Tel 1 800 227 5980 / 1 510 259 0500 Fax 1 510 259 0600

Campbellville, Canada  
Tel 905 854 5650 Fax 905 854 5653

Guadalajara, Mexico  
Tel +52 (33) 3689 1146 Fax +52 (33) 3689 2240

Livingston, Scotland  
Tel +44 (0)1506 420420 Fax +44 (0)1506 403919

Brisbane, Australia  
Tel +61 (0)7 3877 6333 Fax +61 (0)7 3343 8371

Singapore  
Tel +65 6273 6362 Fax +65 6273 8161

Over 30 Offices Worldwide

[www.heatandcontrol.com](http://www.heatandcontrol.com) • [info@heatandcontrol.com](mailto:info@heatandcontrol.com) • ©2005 Heat and Control, Inc.